



TONDO 12

120V PENDANTS

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Cord-hung, cable-hung or stem-mount pendant with handcrafted glass diffuser.

LAMPING

Standard: 150W A21 120V incandescent, lamp not included. Dimmable with standard incandescent dimmer (not included).

CFL: 26W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 26W max, 120V, lamp not included.

LED: 11W Replaceable source, 120V, dimmable, 80+ CRI, 3000°K CCT, 1100 lumens, 30,000 hours. Lamp included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 6.25" Dia. x 12" H

Opening sizes: 3x10mm holes.

SUSPENSION

Cord-hung: 10' SJT-type cord. Jacket coordinates with metal finish. 5" Dia. canopy is stamped steel. Black or white powder-coat.

Cable-hung: 1x 10' aircraft-quality stainless steel cable support with 10' AWM-type cord. Jacket coordinates with metal finish. 5" Dia. dome canopy is plated stamped steel. Bronze or Satin Nickel.

Stem-mount: 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.


LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).

Consult factory concerning lower wattage labeling for energy requirements.



TONDO 12 SHOWN IN CARRERA (412019) & HONEY (4120HN)



412007
OPAL MATTE

4120VM
VANILLA MATTE



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 1/17




ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH	OPTIONS
Cable Fixture 1KX 1 Lt. Dome	412007 Opal Matte 412019 Carrera 4120HN Honey	(blank) 150W A21 Incan I1 26W TBX 120V R1 26W TBX 277V	Cable/Stem Fixture BR Bronze SN Satin Nickel	L 15' cord LW Low wattage labeling
Stem Fixture 1TT 1 Lt. Flat	4120VM Vanilla Matte	GU24 26W GU24 120V LED 11W LED 120V, dimmable	Cord Fixture BK Black (Black cord) WH White (White cord)	
Cord Fixture 1VC 1 Lt. Dome 1VT 1 Lt. Flat				

Ex. **1KX-412019-SN**
Tondo 12 Pendant w/ Carrera Glass,
Satin Nickel Finish


PENDANT OPTIONS:

CORD-HUNG PENDANTS




- Flat or Dome Canopy styles. Dome style allows adjustment without cutting cord.
- Suitable for sloped ceilings
- Cord: 10' SJT, 5" sleeve at socketholder
- Black or White finish

CABLE-HUNG PENDANT



- 1x 10' aircraft-quality stainless steel cable
- Suitable for sloped ceilings
- 1x lampholder
- 4-pin CFL options available
- Cord: 10' AWM-type provided
- Bronze or Satin Nickel

STEM PENDANT



- Swivel at canopy, suitable for sloped ceilings
- Includes telescoping section plus 4 connectable stem sections, (1x 3", 1x 6", 1x 12", 1x 18"), 10' max
- Bronze or Satin Nickel

ACCESSORIES:

ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length, up to 10' max. Telescoping adjustable section allows up to 3" movement.

- T20A-SN** or **T20A-BR** Adj. Section
- T203-SN** or **T203-BR** 3" Section
- T206-SN** or **T206-BR** 6" Section
- T212-SN** or **T212-BR** 12" Section
- T218-SN** or **T218-BR** 18" Section

LONGER CORD LENGTHS:

Longer cord length of 15' available. Add an "L" to the end of the item number, i.e. 1JC-169707-SNL.

LOW WATTAGE LABELING:

Incandescent fixture supplied with 16 watt relamp label. Add an "LW" to the end of the item number, i.e. 1JC-169707-SN-LW.

Project Information: